

RJ45防塵蓋資訊模組

*單體測試通過TIA/EIA568-B-2.1

ISO/IEC-11801 EN 50173 2nd version 標準.

*防塵蓋設計可防止灰塵造成接觸不良,安裝維修簡便.

*高密度體積小可安裝在1U 24Port面板

*不需專用工具即可施工

*T568-A/B 雙線位標示.

*模組外殼及防塵蓋板可選用多種顏色.

*符合TIA-606管理系統規範.

*線材可依線位排列以束線帶固定後安裝,不易脫落及錯位

Certificate

UL CSA ETL 3P

Standards

TIA/EIA 568-B2

ISO/IEC 11801 2nd version

EN-50173 2nd version

Applications

Gigabit Ethernet

ATM2.4G/1.2G/155/622

TP-PMD

ADSL

ISDN

Features

T-568A/B wiring

RJ 45 complies with FCC

IEC 68 part 2-3 standard

110/Krone universal IDC connector

Provides termination for

22~26 AWG wire

Specifications

Housing is fire-resistance ABS

Contacts are 50u" gold-plated / 100u" Nick

Insertion life cycles >750

IDC >250 cycles

Contact resistance : 20M ohm

Current rating : 1.5Amps

DC resistance: Max.0.1ohm

Insulation material:Polycarbonate(meet UL-94V-0)



Part NO	Description	TYPE	Std.Pkg. Qty
5EUTPKYWH-LC	C5E RJ45 Keystone WH	UTP	10/100/1000
5EUTPKYBU-LC	C5E RJ45 Keystone BU	UTP	10/100/1000
C6UTPKYWH-LC	C6 RJ45 Keystone WH	UTP	10/100/1000
C6UTPKYBU-LC	C6 RJ45 Keystone BU	UTP	10/100/1000
TLR4T01GR-LC	TEL RJ11 Keystone GR		10/100/1000